

ACCESSORIES

Smart touch control



- 3,5" TFT full touch-screen colour graphic display control panel for EQ range of HVLS fans.
- Provides a single point of control for up to 4 units.
- RS-485 ModBus connection.

Downrod



- Downrod made from galvanised steel.
- Different length downrod on request.


Description	Weight (kg)	Dimensions (mm)
TUB1500	6,6	50x50x3 - L=1500

Speed controller




- Potentiometer with front knob to adjust the motor speed.
- Provided with two-pole switch (ON/OFF).
- Front yellow led to indicate that the load is active.
- Controls one fan only.
- 230V~ 50/60Hz.
- Supplied with IPX55 wall surface box.

I-Beam



- I-Beam fixing kit suitable for standard IPE, HEA and HEB profiles.
- Fixing screws supplied.

Glulam



- Fixing kit suitable for rectangular beams with base between 100mm and 260mm.
- Fixing screws supplied.

Aesthetic hub cover



- Aesthetic hub cover made from robust plastic material.



REFRESH[®]
Fans inc.

Efficient. Effective. Essential.

Canada:
Refresh Fans Inc. - 200 West Beaver Creek Road, Unit 15
Richmond Hill, ON - L4B 1C7

USA:
Refresh Fans Inc. - 6601 Lyons Road, Unit H-3
Coconut Creek, FL - 33073

www.refreshfans.com